

# DATASHEET

## **AQUA**scat<sup>®</sup> 1000LT

### Suspended sediment profiler - lite



## Suspended sediment in the field - to 200m

**IDEAL FOR SEDIMENT RESEARCH AND SURVEYS**

#### **KEY FEATURES**

- Uses acoustic backscatter method
- 2 different frequencies
- Fixed transducers for repeat deployments

#### **APPLICATIONS**

- Sediment transport studies
- Dredge monitoring
- Water quality monitoring

## SPECIFICATION

Sediment range	Sensitive to a wide range of grain sizes Size inversion typically feasible for 20 µm to 500 µm radius Typically 0.01 g/l to 20 g/l over 1 m, or more over shorter range
Frequencies	2 frequencies - 1 MHz, 4 MHz
Transducers	Ø10-20mm ceramic discs (beam width according to frequency)
Transducer arrangement	2 fixed transducers
Gain	Software controlled transmitter and receiver gain adjustment
Range	150 cm (typical) at 4 MHz, 255 cm at 1 MHz
Transmitted signal	1 W rms typical transmit CW pulse, pulse length to match cell size.
Transmission rate	128 Hz max pulse rate for each frequency (i.e. 256 pulses per second for two), subject to acoustic range limits. Minimum rate 1 Hz for calibration.
Data averaging	Cell ensembles averaged over time by powers of 2 up to 64 before storage
Range cells	256 cells, 10 mm (at 1500 m/s speed of sound)
Burst duration	Defined by number of profiles requested.
Burst trigger	Either external hardware trigger when required or internal software trigger at regular intervals
Burst interval	Internally generated from once every minute to once every 255 minutes, user definable start time of first burst.
Trigger output	A digital output allows triggering of external instruments
Power requirement	8 V to 24 V dc. Typically 1 W when logging, and with standby of typically 1 mW when not logging.
Battery packs	Internal rechargeable Nickel Metal Hydride battery pack gives up to 5 days typical burst deployment. External battery packs available according to deployment needs.
Additional sensors	Built-in temperature and pressure
Disk storage	Compact Flash (proprietary format). 8 GB standard.
Data comms	USB 1.1 typically 2-3 Mbaud
Housing options	200 m rated acetal housing.

## Contact us

**t** +44 (0)1256 416010 (UK) **t** 1-281-220-6035 (USA)  
**e** [inquiry@aquatecgroup.com](mailto:inquiry@aquatecgroup.com) [www.aquatecgroup.com](http://www.aquatecgroup.com)

AQUAsc<sup>®</sup> is a registered trademark of Aquatec Group Limited. All trademarks & registered trademarks are acknowledged. Aquatec reserves the right to make changes to the specifications contained in this document without notice in the interests of maintaining or improving product quality. Document copyright © 2016 Aquatec Group. AQSLTD - Feb16v1.



De Hoogjens 22  
 4254 XW  
 Sleeuwijk  
 The Netherlands

Tel: +31-183-307900  
 Fax: +31-183-307910  
 Email: [info@seascape.nl](mailto:info@seascape.nl)  
[www.seascape.nl](http://www.seascape.nl)