

CSP-S Seismic Energy Source



The **CSP-S** is a compact 'all-in-one' power source for marine sparker applications, specifically the Applied Acoustics' Delta Sparker. The unit can be supplied as a 1250J, 4000J, 6000J or 12,000J variant that allows for subsequent upgrade.

The high charge rate allows for fast, high energy sound pulses from sparker and in addition, lower power settings are available for single boomer and S-boom applications.

Key Features

- High energy level for increased penetration
- High current and voltage solid state (semi-conductor) discharge method
- Meets EC emissions regulations enabling interference-free field use
- All settings externally selectable
- No requirement for extra separate capacitor bank
- 300J setting for boomer applications (except CSP-S12000)
- Variable Input Power Circuitry for 'soft start'
- Additional safety/protection features
- CSP-S1250 designed for high performance boomer application or part of S-Boom System
- Supplied in robust transit case, with HV junction box (HVJ3000), mains lead and HV connector plug

Technical Specification

PHYSICAL

CSP-S1250/S4000/S6000

Size Transit Case with wheels (12U) with cover in place and handles flat:
68cm(H) x 58cm(W) x 92cm(D)

Weight Case and cover: S1250, 92kg S4000, 106kg S6000, 114kg

CSP-S12000

Size Transit case (21U) with covers in place and lifting eyes/handles flat:
116cms(H) x 69cms(W) x 96cms(D)

Weight Case and cover: 183kg

CSP-S Technical Specification continued...

ELECTRICAL SPECIFICATION

Mains Input	110 or 240Vac (fixed) 45-65Hz@5.0kVA single phase 3 pin connector Variable input power circuitry (AVIP) 'soft start' circuitry		
Voltage Output	2500 to 3950Vdc, 4 pin interlocked connector. Solid state semi-conductor discharge method		
Output Energy	Externally selectable in Joules (20 increments)		
	CSP-S1250:	100-1250J	CSP-S4000: 300-4000J
	CSP-S6000:	300-6000J	CSP-S12000: 600-12000J
Charging Rate	2500J/second for continuous operation at 0-45°C		
Capacitance	CSP-S1250:	176µF, 10 ⁸ shot life	CSP-S4000: 512µF, 10 ⁸ shot life
	CSP-S6000:	800µF, 10 ⁸ shot life	CSP-S12000: 1536µF, 10 ⁸ shot life
Trigger	+ve key opto isolated or isolated closure set by front panel switch, BNC connector on front panel and remote box (optional)		
Repetition rate	6pps max Limited by charge rate, energy level and sound source rating		
Earth	M8 stainless steel stud on front panel		

SAFETY FEATURES

- Main electronic control circuits and secondary layer of safety circuitry
- Specially designed HV connector with interlock
- High speed dump resistors for high voltage components
- Capacitor bleed resistors
- Open circuit shutdown
- Timer shutdown
- Output current monitor and shutdown
- Over temperature shut-down
- Cover and connector interlocks
- HV fault indicator for internal temperature, low input voltage or capacitor fault
- Remote control available for triggering and operation

The unit's internal design has a modular construction for ease of servicing and capacitor replacement. However, for safety reasons, only Applied Acoustics trained engineers should attempt a repair.

COMPATIBLE SOUND SOURCES

CSP-S1250	AA201, AA251, AA301, Squid 501, Squid 2000, S-Boom
CSP-S4000/CSP-S6000	AA201, AA251, AA301, Squid 501, Squid 2000, S-Boom, Delta Sparker
CSP-S12000	Squid 501, Squid 2000, Delta Sparker



Due to continual product improvement, specification information may be subject to change without notice.
CSP-S Seismic Energy Source/June 2014
©Applied Acoustic Engineering Ltd.



Applied Acoustic Engineering Ltd

T +44 (0)1493 440355
F +44 (0)1493 440720
E general@appliedacoustics.com
W www.appliedacoustics.com